SLOW

Technical sheet

CHARACTERISTICS	VALUES		UNITS	STANDARDS
	WARP	WEFT		
GENERAL CHARACTERISTICS				
Composition	33% Recycled Sunbrella Acrylic 65% Sunbrella Acrylic 2% Polyester			
Backing / Finish	Non PFAS - Water-repellent & Stain-proof			
Weave	Jacquard			ISO 7211-1
Weight	470		g/m²	ISO 3801
Width	140		cm	EN 1773
Roll length	35		ml	
FABRIC RESISTANCE				
Tensile strength	124	90	daN/5cm	ISO 13934-1
Elongation at break	18	30	%	ISO 13934-1
Pilling	5		Class / 5	ISO 12945-2
Spray test	5		Class / 5	ISO 4920
Seam slippage (180 N)	< 0.3	< 1	mm	ISO 13936-2
Stitching strength	550	570	N	ISO 13935-2
Stability on 30 deg. C washing	-1.8	-0.5	%	ISO 5077
COLOUR-FASTNESS				
Colour fastness UV - outdoor - 1000h	4-5		Class / 5	ISO 105 B04
Colour fastness UV - indoor	8		Class / 8	ISO 105 B02
Colour fastness under dry friction	5		Class / 5	ISO 105X12
Colour fastness under wet friction	5		Class / 5	ISO 105X12
Colour fastness 30°C washing	5		Class / 5	ISO 105 C06
FIRE RESISTANCE				
California Technical Bulletin 117-203 Section 1	PASS			
NFPA 260 Classe I	PASS			
NF EN 1021-1	PASS			
BS 5852 Part 1 Source 0	PASS			
USES				
Guarantee	5		years	
Recommanded Uses	Seating, Cushions			

CARE

This product's values may vary with a tolerance of ± 5%

Dickson-Constant SAS, [French limited-liability corporation] with capital of €12,640,000 - Metropolitan community of Lille business registration
10, rue des Châteaux - BP 109 - Z.I la Pilaterie 59443 Wasquehal cedex - France
Tél. : +33.(0)3.20.45.59.59 - Fax : +33.(0)3.20.45.59.00 - www.dickson-constant.com/en/UK